

# AIS 026 CYCLONE

---

## PRODUCT DETAILS

PRODUCT DETAILS | FEATURES | SPECIFICATIONS |  
WARRANTY INFORMATION



One of the key reasons our incinerators are recognized as being *'probably the best'* on the world market is the use of our market leading and trusted low thermal mass monolithic concrete lining which is used in all of our models.

All models in the Cyclone Range are supplied with an integral secondary chamber, ensuring they fully conform to many legislative bodies around the world.

## AIS 026 Cyclone

- Ideal for the bio secure disposal of carcasses within the agricultural farming industry, particularly suited for small to medium farming operations; Sheep, Piglets, Poultry, Game Farms.
- Access to the main chamber is via a loading door located on the front of the machine.
- PLC timer controls with automatic burner shut off function and fast ignition burners. One temperature-controlled burner in the main chamber and one in the secondary chamber.
- Burns up to \*54kgs/120 lbs per hour and has a load capacity of up to 190kg / 419 lbs.
- Can be loaded whilst in operation maximizing the inherent thermal efficiency of our trusted monolithic concrete lining, keeping running costs low.
- Optional Extra features include; Animal Loading Trolley / Winch assembly / USB Data Logger / Stack Extensions / Ash Rake / Simple Heat Exchange system / Control Panel screen size increase / Service Kits .



AIS 026 Cyclone Main Chamber View

\* Burn Rate may be subject to your local regulations. Speak to a member of our team for more information.

Image shown is of the AIS 026 Cyclone



### Be Assured of a Quality Product & Quality Service with AIS:

- Each machine is hand crafted by our team of skilled technicians in the UK and U.S.
- The reason your incinerator will last is due to the type of lining used. Our trusted monolithic casting system ensures maximum strength, reliability and a longer machine life. We are always happy to explain why our technology is far better than any other manufacturers product on the world market. Talk to us to find out more and make your own mind up.
- Behind the AIS brand is a team of experts who are always on hand to discuss any questions that you may have about incineration, so you can be assured of great service and a great product.
- But it goes beyond that, we stay with you for the life of the machine, always on hand if or when you need us. It's a people thing, it's an AIS thing.

### \*3 YEAR WARRANTY AS STANDARD :

The whole plant and associated equipment supplied as part of the overall installation will be covered by a \*36-month or 2100 hours warranty (whichever soonest) from the date of dispatch from the manufacturing premises of Agri Incineration Systems Limited, except for any consumable item as listed below and provided that:

- a) Each defect has materialized under normal operating conditions and not due to misuse, abuse, or operational errors.
- b) An effective maintenance regime is operated which may include a Service Contract being taken up at the time of handover. This Service Contract should be provided by Agri Incineration Systems Limited or trained and authorized agents.
- c) The contract price, as detailed within the quotation or as amended by agreement of both parties, has been paid in full.

#### Consumable Parts (Items not covered under Warranty).

1. Primary Chamber Thermocouples
2. Secondary Chamber Thermocouples
3. Access Door seals
4. Control Panel indicator bulbs or LEDs
5. Burner electrodes and leads
6. Burner probes and leads
7. Burner Blast Tubes
8. Burner Diffuser Assemblies
9. Burner nozzles / ionization probes
10. Grate Bars
11. Mechanical damage of any sort

*3 Year Warranty as standard, talk to us about a long-term Service Plan to suit you*



Specifications	Unit - Metric		Unit - Imperial	
*Burn Rate	Up to kg/hr	54	Up to lbs/hr	120
Front /Top Load		Front		Front
Operational Dimensions Static (LxWxH)	m	1.9 x 1.7 x 5.1	feet/inch	6' 3" x 5' 5" x 16' 9"
External Height Static	mm *inc. Stack	5100	feet/inch *inc. Stack	16' 9"
External Height Static	mm *ex. Stack	2412	feet/inch *ex. Stack	7' 11"
Weight Static	Tonne *estimated	2.4	lbs *estimated	5292
Load Height from Ground (floor to bottom edge)	mm	325	feet/inch	1' 1"
*Fuel Consumption Diesel	LPH *est during main burn	6.9 – 10.5	GPH *est during main burn	1.8 – 2.8
*Fuel Consumption LPG	LPH *est during main burn	9- 16		1.7 – 4.1
*Fuel Consumption Nat Gas	m³/h *est during main burn	7- 10	ft³/h *est during main burn	243 – 370
Grate Bars		No		No
Load Door Opening (Width x Height/Depth)	mm *area	900 x 710	ft/inch *area	2' 11" x 2' 4"
Chamber Size (LxWxH)	m	1.2 x 0.9 x 0.7	ft/inch	3' 10" x 2' 11" x 2' 4"
Chamber Actual Volume	m³	0.74	ft³	26
Chamber Load Volume	m³	0.34	ft³	12
*Chamber Load Capacity	kg	190	lbs	419
Std Stack Diameter	inch/mm *2D Size	10"	inch/mm *2D Size	10"
No. Main Burners		1		1
No. Secondary Burners		1		1
Burner Output	kW *heat	152	Btu *heat	518,646
Electric Consumption	kW *electricity	0.25	kW *electricity	0.25

\*The optimum performance of the incinerator is dependent upon efficient usage and waste type